

Parabolic Antennas

Model	Frequenzy (MHz.)	Band (MHz.)	Gain (dBi)	VSWR	F/B	Feed Source	Dimension (mm)	Weight
D5800P29A60-1	4.900 ~ 5.850	600	29	1.5	35	Waveguide	ø600	5.000gr.
D5800P32A90-1	4.900 ~ 5.850	600	32	1.5	40	Waveguide	ø900	10.000gr.
D5800P35A120-1	4.900 ~ 5.850	600	35	1.5	42	Waveguide	ø1.200	12.500gr.
D5800P36A150-1	4.900 ~ 5.850	600	36	1.5	45	Waveguide	ø1.500	15.000gr.
D5800P22A30-2	4.900 ~ 5.850	900	22	1.5	36	Circular	ø300	3.500gr.
D5800P29A60-2	4.900 ~ 5.850	900	29	1.5	30	Circular	ø600	5.000gr.
D5800P32A90-2	4.900 ~ 5.850	900	32	1.5	40	Circular	ø900	10.000gr.
D5800P35A120-2	4.900 ~ 5.850	900	35	1.5	42	Circular	ø1.200	13.000gr.



D5800P22A30-2



D5800P29A60-2



D5800P29A60-1

Parabolic Antennas

Model	Frequenzy (MHz.)	Band (MHz.)	Gain (dBi)	VSWR	F/B	Feed Source	Dimension (mm)	Weight
D5800P22A30-3	4.900 ~ 5.850	125	22	1.4	30	Coaxial	ø300	2.500gr.
D5800P29A60-3	4.900 ~ 5.850	125	29	1.4	35	Coaxial	ø600	4.000gr.
D5800P32A90-3	4.900 ~ 5.850	125	32	1.4	40	Coaxial	ø900	6.500gr.
D5800P35A120-3	4.900 ~ 5.850	125	35	1.4	42	Coaxial	ø1.200	10.000gr.
D5800P36A150-3	4.900 ~ 5.850	125	36	1.4	45	Coaxial	ø1.500	15.000gr.
D5800B16A03	5.725 ~ 5.850	125	16	1.4	30	%	ø260	2.500gr.



D5800P22A30-3



D5800P29A60-3



D5800P32A90-3